Spray Calibration and Set-Up Dr. Phil Busey, CCA, CPAg¹ May 25, 2016 South Florida STMA at JetBlue Park, Fort Myers, FL



Getting a prediction for tomorrow's wind speed and rain probability.

Search Google for "national weather service Tampa Bay" or other big city, Miami, Melbourne Click the top link, e.g., http://www.srh.noaa.gov/tbw/	Code with a finish to the code of the code
Look down the page for the map that says, "Click on the map below for the latest forecast" and click the map.	The branch of th
Look for a new map to appear with a bright green square which is the "Forecast Area." Click again if you need to reposition the square on your area of interest. Make sure the square is centered over land, not ocean.	Vitins Vitins Protein Freed in the Cort (5 - Park - Par
In the new page that emerges, look to the lower right to see the "HOURLY WEATHER GRAPH" and click it.	Notiny Weather Forecast National Digital Forecast Database
The "Hourly Weather Forecast Graph" will appear and it will have instructions how to go "Forward 2 Days" (at your peril) and "Back 2 days." There is also a link to the left under "Additional Forecasts and Information" for "Tabular Forecast" For today this says at 7:00 am precipitation 10% going down to 0% and wind 8 mph go up to 11 mph.	Simple S

¹ Certified Crop Adviser and Certified Professional Agronomist and member of Brookside Society of Professional Consultants.

How NOT to spray (don't do anything on this list)

- 1. Not reading the label
- 2. Wind speed over 5 mph or other weather problems (rain)
- 3. Not having everything ready the day before including replacement nozzles
- 4. Not having the right pesticide
- 5. Pump or hoses leaking
- 6. Spray nozzles not identical or the wrong kind
- 7. Other parts of spray equipment not working, e.g., foam marker, pressure gauge
- 8. Hoses blocked
- 9. Previous pesticide not cleaned out
- 10. Agitator not working
- 11. Wrong boom height
- 12. Ground speed not controlled
- 13. Failure to follow up with a second properly timed application
- 14. Being unable to read the bottom of the tank
- 15. Not properly calibrating or not properly using hand sprayer
- 16. Using hollow cone nozzles for spot treatment
- 17. Mixing too many things in the tank
- 18. Adding extra adjuvant beyond that called for on the label or the wrong adjuvant
- 19. Using flood jet nozzles for herbicides
- 20. Using an overlap between passes that is different from the overlap of nozzles on the boom

Learn nozzle tip selection by reading the manufacturer's handbook




	PSI						
	15	20	25	30	40	50	60
XR8001	M	F	F	F	F	F	F
XR80015	M	M	M	F	F	F	F
XR8002	M	M	M	M	F	F	F
XR8003	M	M	M	M	M	M	F
XR8004	C	C	M	M	M	M	M
XR8005	C	C	C	C	M	M	M
XR8006	C	C	C	C	C	С	C
XR8008	VC	VC	VC	C	C	C	C
XR11001	F	F	F	F	F	VF	VF
XR110015	F	F	F	F	F	F	F
XR11002	M	F	F	F	F	F	F
XR110025	M	M	F	F	F	F	F
XR11003	M	М	M	F	F	F	F
XR11004	M	M	M	M	M	F	F
XR11005	М	M	M	M	M	M	F
XR11006	C	С	М	М	M	M	M
XR11008	C	С	C	C	С	М	M
XRC11010	VC	VC	C	C	C	C	M
XRC11015	XC	XC	VC	VC	C	C	C
XRC11020	XC	XC	XC	VC	VC	VC	VC


XR TeeJet® (XR) and XRC TeeJet (XRC)

How to calculate gallons per acre (GPA) knowing ground speed, nozzle discharge, and nozzle spacing.


Long version



Simplified version



Working version



APPLICATION METHODS, MIXING, AND COMPATIBILITY

Uniform, thorough spray coverage is important to achieve consistent weed control. Select spray nozzles and pressure that deliver MEDIUM spray droplets as indicated in nozzle manufacturer's catalogs and in accordance with ASAE Standard S-572. Nozzles that deliver COARSE spray droplets may be used to reduce spray drift provided spray volume per acre (GPA) is increased to maintain coverage of weeds.

Mixing Instructions

Revolver Herbicide must be applied with clean and properly calibrated equipment. Prior to adding Revolver Herbicide, ensure that the spray tank, filters and nozzles have been thoroughly cleaned.

. Fill spray-tank with 25% to 50% of the required volume of water and begin agriculton prior to the addition of Revolver Herbicide.

- 2. Continue agitation to ensure full dispersion of Revolver Herbicide.
- If Revolver Herbicide is applied in a tank mixture with other pesticides, add Revolver Herbicide to the spray tank first and ensure it is thoroughly dispersed before adding other pesticides.
- 4. Continue to fill the spray tank with water to the desired volume and agitate while adding spray adjuvants and nitrogen fertilizers. Continue agitation during application to ensure a uniform spray mixture.

Application

Broadcast:

Revolver Herbicide can be applied as a broadcast treatment in minimum of 25 gallons of water per acre. For weed control in dense weed populations or under adverse growing conditions, use higher spray volumes up to 60 gallons per acre. Rates are listed in the Use Rate Table for Weed Control.

Spot treatment:

For hand held pump type sprayers, mix 0.5 to 2 fluid ounces of Revolver Herbicide per gallon of water, depending on the weed and stage of growth. Use the higher rate for the more difficult to control or larger weeds. Spray to wet. Do not apply beyond runoff.

SPRAY SOLUTION pH

The efficacy of Revolver Herbicide may be affected by the pH of the spray solution. A pH near 7 is ideal. If pH is less than 6, add a buffer.

Excerpts from an herbicide label showing a few examples how the label determine what spray equipment is used and how it is used.

WEED CONTROL

Tank Additions for Difficult-to-Control Weeds

Control of some difficult-to-control weeds with Revolver Herbicide, including volunteer/clumpy ryegrass, and goosegrass, may be improved by additional adjuvant and nitrogen fertilizer. These additives may also cause phytotoxicity to desirable grasses under some situations. Use of these additives should be tested in a limited area prior to widespread use

- Use methylated or ethylated seed oil containing at least 80% MSO and 10% emulsifier or greater (up to 1 % v/v). Do not use non-ionic surfactants, crop oil concentrates, crop oil concentrate/methylated seed oil blends, and refined vegetable oils with Revolver Herbicide.
- Sources of nitrogen include ammonium sulfate (AMS) and urea ammonium nitrate (UAN). Use UAN (1.5-2 qt/A) in areas of low relative humidity and spray grade AMS (1.5-3 lb/A) for areas of high relative humidity.

TANK CLEANUP PROCEDURE

- Drain the tank completely, then wash out tank, boom and hoses with clean water. Prain again.
- Fill the tank half full with clean water and add ammonia (i.e. 3% domestic ammonia solution) at a dilution rate of 1% (i.e. 1 gallon of domestic ammonia for every 100 gallons of rinsate). Completely fill the tank with water. Agitate/recirculate and flush through boom and hoses. Leave agitation on for 10 minutes. Drain tank completely.
- 3. Repeat Step 2
- Helmove nozzles and screens and soak them in a 1% ammonia solution. Inspect nozzles and screens and remove visible residues.
- 5. Flush tank, boom, and hoses with clean water.
- 6. Inspect tank for visible residues. If present, repeat Step 2.